



Drawing Nr.	HOLE DIA
05AA	0.052 [1.32]
05AB	0.062 [1.57]

www.interplexnas.de | www.interplex.com/NAS

SELECT SPECIFIC OPTIONS TO DETERMINE ORDERING CODE:

TYPE	PITCH (P)	DRWG. NO.	SOLDER LOCATION	GAP (G)	SOLDER TYPE	SOLDER STOP	STAND OFF (SO)	MATERIAL/ PLATING	STANDARD ORIENTATION
B = SIP	A = .100[2.54]	05AA 05AB	S = Bottom O = No Solder	22 = .022[0.558] 26 = .026[0.661] 31 = .031[0.787] 36 = .036[0.914] 41 = .041[1.04] 46 = .046[1.17] 52 = .052[1.32] 56 = .056[1.42] 62 = .062 [1.575]	See Chart on Page 9	O = No Stop S = Stop	A = .040[1.00] D = .070[1.77] K = .145[3.68]	E = Phosphor Bronze Pre-Plated 100% Sn K = Phosphor Bronze Post-Plated 100% Sn C = Phosphor Bronze Pre-Plated Sn60/Pb40 H = Phosphor Bronze Post-Plated Sn60/Pb40	F = Winding (SB)

CODE:

--	--	--	--	--	--	--	--	--	--